

WEIGHT	25 LBS
HEIGHT	18"
WIDTH	10.75"
DEPTH	18"
FLUE SIZE	4" DIAMETER
FUEL CONSUMPTION	1.3 gal/24 hr - Low 3.2 gal / 24hr - High
HEAT OUTPUT	6,500 BTU - 16,250 BTU
WATER COIL	Optional Single or Double Turn
COMBUSTION ASSIST FAN	Standard 12V DC
INSTALL CONSIDERATIONS	Install facing bow or stern or retrofit valve to side.

**LOFOTEN**  
Diesel Heater**Model #00-LOF****Product Includes:**

- Black heat shroud
- Remote mounted speed control (12v, 24v or 32v),
- Hold down strap
- Finishing (drip) pan
- Flame viewing window
- Small Cast-Iron cooktop

**Options:**

- Single turn hot water coil installations
- fan voltage options
- valve calibration for diesel (standard) stove oil or kerosene
- special order side-mounted valve (for athwartship mounting in sailboat)

The LOFOTEN diesel heater is our only heater model to include a cooking surface. It features the efficient 6" Stainless Steel burner. This stove is great for producing heat for heating your boats cabin or, for smaller boats, the whole boat. The heat can be extended by producing hot water with the optional water coil heat exchangers for remote heating or for showers etc. The heaters reach can further be extended with the use of the Heatex stack robber system.

This stove uses 4 inch diameter flue components. Use with Dickinson stainless steel flue pipe, 45 degree elbows, barometric dampers, deck-fittings and exhaust caps. Fuel pumps and filters are available or you can use a gravity tank. Installation guidelines require a minimum 4 foot flue rise and heat clearances of 6 inches or a min of 2 inches to an insulated surface. See the Lofoten owner's Manual for details.

Standard fuel metering for this stove is the Dickinson 3D valve for diesel. Stove Oil (3S) and Kerosene (3K) are also available as options or add ons. A 12vdc assist fan is standard for start up or high fire burn. 24v and 32v available as options or add ons.