

# HB Poly

PRODUCT CODE: 307



This lightweight, economical twine is UV-stabilized, easy to splice, and it floats.


## APPLICATIONS

## FEATURES AND BENEFITS

## SPECIFICATIONS

FIBER: Polypropylene  
SPECIFIC GRAVITY: 0.91  
SPLICE/CLASS: Product Specific Class I

ELASTIC ELONGATION PERCENTAGE:  
At % of break strength  
10%.....4.50%  
20%.....5.50%  
30%.....6.50%



COLOR: Green or yellow

DIAM. (inch)	CIRC. (inch)	WEIGHT PER 100 FT. (lbs)	AVG. STRENGTH (lbs)	MIN. STRENGTH (lbs)	DIAM. (mm)	CIRC. (mm)	WEIGHT PER 100 M (kg)	AVG. STRENGTH (kg)	MIN. STRENGTH (kg)
3/16"	9/16"	0.60	750	680	5	15	0.89	340	310
1/4"	3/4"	1.1	1,200	1,100	6	18	1.6	540	490
5/16"	1"	1.6	1,700	1,500	8	24	2.4	770	690
3/8"	1 1/8"	2.3	2,600	2,300	9	27	3.4	1,200	1,100
1/2"	1 1/2"	3.7	4,300	3,800	12	36	5.5	1,900	1,700

Specifications are for spliced strengths.