




BUILT FOR THE RIGORS OF THE MARINE INDUSTRY

USER FRIENDLY, LOW TEMP APPLICATION

DOESN'T CRACK OR SHRINK

FLEXIBLE & PAINTABLE



REMOVABLE

SEMI-PERMANENT

PERMANENT

The second second	PERMANENT	REMOVABLE	SEMI-PERMANENT
ANCHORTECH	PREMIUM FAST DRY ADHESIVE SEALANT	ADVANCED HYBRID SEALANT	RESISTANT ADHESIVE SEALANT
ABOVE WATERLINE USE	х	X	х
ABOVE & BELOW WATERLINE USE	X		
PAINTABLE	24 HOURS	30 MINUTES	1 HOUR
RETURN TO SERVICE TIME	24 HOURS	30 MINUTES	1 HOUR
UV RESISTANT		X	X
TEMPERATURE RANGE	41°F TO 100°F	20°F TO 120°F	20°F TO 120°F
SEALING ACRYLIC WINDOWS		x	
MOLD AND MILDEW RESISTANT	BANK	X	X
ADHESIVE SEALANT FLEXIBLE	ADHESIVE SEALANT FLEXIBLE	SEALANT FLEXIBLE	ADHESIVE SEALANT FLEXIBLE
DAMP AND DRY APPLICATION FRIENDLY	X	X	X
COVERAGE	24.3 LINEAR FEET @ 1/4" DIAMETER BEAD	49 LINEAR FEET @ 3/16" DIAMETER BEAD	55 LINEAR FEET @ 3/16" DIAMETER BEAD
COLORS	WHITE, BLACK	WHITE, CRYSTAL CLEAR	WHITE

PERFECT PICK GUIDE

PREMIUM FAST DRY ADHESIVE SEALANT SEALING BILGES, STERN JOINTS AND FILLETS, DECK FITTINGS, FIBERGLASS DECK TO FIBERGLASS HULL, WOOD TO FIBERGLASS, UNDERWATER LIGHT INSTALLATION, TEAK DECKS TO PLYWOOD, BONDING OR SEALING THE HULL, SEALING AREAS OF FUEL EXPOSURE, THRU-HULL FITTINGS AND DRAIN PLUGS

ADVANCED HYBRID SEALANT GASKET ADHESIVE, DECK HARDWARE, SEALING WINDOWS, HATCHES AND PORTHOLES, BATH AND SHOWER APPLICATIONS, TOE RAILS AND RUB RAILS, WINDOW AND DOOR TRIM, BEDDING PLASTIC FITTINGS, ELECTRICAL HATCH SEALING, DASHBOARD COMPONENTS, NAVIGATION LIGHT INSTALLATIONS

UV RESISTANT ADHESIVE SEALANT ELECTRONICS INSTALLATION, DECK TO HULL, DECK HARDWARE BEDDING AND SEALING, WINDOW AND DOOR FRAMES, NAVIGATION LIGHTS, DECK HATCHES AND PORTHOLE FRAMES, MAST STEPS, RUB RAIL REPAIR OR REPLACEMENT, SCUPPER INSTALLATION, BOW RAIL AND STANCHION INSTALLATION

ADHERES TO

FIBERGLASS • WOOD • ALUMINUM • MOST METALS
MOST PLASTICS • GLASS • AND MOST COMMON BOAT BUILDING MATERIALS



A

UV FAST

PETITI HYBRID